


Habitat ACCESSORIES

14 Modules capacity per row. Earth and neutral bars are installed in isolated supports snapped on to the frame



Enclosure is installed in the wall by turning the fixing screws clockwise



Removable and pre-moulded upper and lower walls provide easy wiring. Cable ties attached to the flanges allow a right conduit connection



Sealable cover is clipped on the frame. A tool must be used for its opening (under normatives)



Distance between rails is of 150 mm

ACCESSORIES

- | | | | |
|--|--------------|----------------------------------|--------------|
| ■ Cover lid for 30P14 | 74702 | ■ Hollow wall fixing element* | 94037 |
| ■ Cover lid for 30P28 | 74712 | ■ 14/28/42 modules DIN Rail | 92765 |
| ■ Cover lid for 30P42 | 74722 | ■ 6 entries earth & neutral bar | 92303 |
| ■ Earth and neutral bar support under pressure | 77540 | ■ 10 entries earth & neutral bar | 92304 |
| ■ White modules-cover lid | 77600 | ■ 14 entries earth & neutral bar | 92301 |

| WINDOWS | OPAQUE | TRANSPARENT |
|------------|--------|-------------|
| | Code | Code |
| 14 modules | 76902 | 76909 |
| 28 modules | 76912 | 76919 |
| 42 modules | 76922 | 76929 |

EARTH AND NEUTRAL BARS STRUCTURE

| Box type | Bar Code | Terminal I | | Terminal II | |
|----------|----------|------------|------|-------------|------|
| | | N | E | N | E |
| 30E-PH14 | 92301 | 12+2 | 12+2 | | |
| 30E-PH28 | 92304 | 8+2 | 8+2 | 8+2 | 8+2 |
| 30E-PH42 | 92301 | 12+2 | 12+2 | 12+2 | 12+2 |

Connectors: 2xØ 5,5 mm. 16 mm²
8-12xØ 4,5 mm. 10 mm²

* This accessory is supplied with PH references